

TP-LINK®

The Reliable Choice

> Switch
Preklopnik



Ellabo

NOVO U PONUDI

PREKLOPNICI

TL-SF1016

410kn - 25% **307,50 kn**

Standardi i protokoli
Osnovne funkcije
Priključci
Certifikati
Dimenzije (W*D*H)

IEEE802.3, 802.3u, 802.3x, CSMA/CD, TCP/IP
IEEE802.3x flow control for Full-Duplex Mode and backpressure for Half-Duplex Mode
16 10/100Mbps (Auto MDI/MDIX)
FCC, CE
11.6*7.1*1.7 in. (294*180*44 mm), 19"



TL-SF1024

520kn - 25% **390,00 kn**

Standardi i protokoli
Osnovne funkcije
Priključci
Certifikati
Dimenzije (W*D*H)

IEEE802.3, 802.3u, 802.3x, CSMA/CD, TCP/IP
IEEE802.3x flow control for Full-Duplex Mode and backpressure for Half-Duplex Mode
24 10/100Mbps (Auto MDI/MDIX)
FCC, CE
17.3*7.1*1.7 in. (440*180*44 mm), 19"



TL-SL1226

980kn - 25% **735,00 kn**

Standardi i protokoli
Osnovne funkcije
Priključci

Certifikati
Dimenzije (W*D*H)

IEEE802.3, 802.3u, 802.3x, CSMA/CD, TCP/IP
IEEE802.3x flow control for Full-Duplex Mode and backpressure for Half-Duplex Mode
24 10/100Mbps (Auto MDI/MDIX)
2 10/100/1000Mbps (Auto MDI/MDIX)
FCC, CE
17.3*7.1*1.7 in. (440*180*44 mm), 19"



TL-SG2224WEB

2120kn - 25% **1590,00 kn**

Karakteristike softvera

Standardi i protokoli
Osnovne funkcije

Link Aggregation
VLAN

Kontrolni pristupni popis

Sigurnost i autorizacija

Upravljanje mrežom

Karakteristike

IEEE 802.3, 802.3u, 802.3ab, 802.3z, 802.3ad, 802.3x, 802.1q, 802.1p
Storm Control (Broadcast, Multicast, Unknown unicast)
Port Mirroring
IEEE 802.3ad LACP Link Aggregation
Port Based VLAN
802.1Q Tag-VLAN
MTU VLAN
Based on Port
Based on MAC
Port Security
Static MAC Address Binding
Dynamic MAC Address Binding
Web (Http) Management
Remote Management
Fixed IP Address Setting
VCT (visual cable test)
Port Flow Statistics
TFTP Upgrade

Karakteristike hardvera

Priključci 24 10/100/1000Mbps (Auto MDI/MDIX)
2 Gigabit SFP ports (shared with port 23, 24)
Certifikati FCC, CE
Dimenzije (W*D*H) 17.3*10.2*1.7 in. (440*260*44 mm), 19"



KONVERTER MEDIJA - 1,25 Gbps

TL-SM311LM

330kn - 25% **247,50 kn**

Standardi i protokoli
Kabel
Optička nit
Max. duljina kabela
Sučelje
Certifikati

IEEE 802.3z, CSMA/CD, TCP/IP
Multi-mode Fiber
50/125um or 62.5/125um Multi-mode
550m
LC
FCC, CE



Navedene cijene su veleprodajne i na njih se obračunava PDV