REGULATOR OSVJETLJENJA ROTACIJSKI IZMJENIČNI LED 60W 1M

☐ EM13PW
■ EM13SB
■ EM13AT
■ EM13ES
■ EM13IW

- rotacijski s izmjeničnom sklopkom
- opterećenje:
  LED, 0 – 60 W (maks. 6 LED tinjalica s regulacijom osvjetljenja)
  GLS, 0 – 60 W
- napajanje 230 V~ 50 Hz
- moguća je kombinacija s izmjeničnom sklopkom
- zajedničko montiranje više uređaja u jednu dozu dopušteno je isključivo pod uvjetom da njihovo ukupno maksimalno opterećenje ne premašuje maksimalnu snagu jedne sklopke za zatamnjenje
- dopušteno je korištenje samo jedne sklopke za zatamnjenje po strujnom krugu
- osigurač nije montiran – morate upotrijebiti vanjski osigurač
- sukladno normi IEC60669-2-1
- vijčano pričvršćivanje vodiča presjeka 1,5 – 2,5 mm²

DIMMER ROTATIVE/2WAY LED 60W 1M

- *rotation control with 2-way switch*
- *loads: LED, 0 – 60W (max. 6 dimmable LED lamps)*
  GLS, 0 – 60W
- *supply voltage 230V~ 50Hz*
- *2-way switch combination is possible*
- *installing several devices together in one box is only permitted if their total maximum load does not exceed the maximum power of a single dimmer*
- *one circuit allows the use of only one dimmer*
- *no built-in fuse – external fuse must be used*
- *in accordance with IEC60669-2-1*
- *screw contacts - 1.5-2.5mm²*

REGULATOR OSVJETLJENJA ROTACIJSKI IZMJENIČNI LED 180W 1M

☐ EM14PW
■ EM14SB
■ EM14AT
■ EM14ES
■ EM14IW

- rotacijski s izmjeničnom sklopkom
- opterećenje:
  LED, 0 – 180 W (maks. 20 LED tinjalica s regulacijom osvjetljenja)
  GLS, 0 – 180 W
- napajanje 230 V~ 50 Hz
- moguća je kombinacija s izmjeničnom sklopkom
- zajedničko montiranje više uređaja u jednu dozu dopušteno je isključivo pod uvjetom da njihovo ukupno maksimalno opterećenje ne premašuje maksimalnu snagu jedne sklopke za zatamnjenje
- dopušteno je korištenje samo jedne sklopke za zatamnjenje po strujnom krugu
- osigurač nije montiran – morate upotrijebiti vanjski osigurač
- sukladno normi IEC60669-2-1
- vijčano pričvršćivanje vodiča presjeka 1,5 – 2,5 mm²

DIMMER ROTATIVE/2WAY LED 180W 1M

- *rotation control with 2-way switch*
- *loads:*
  LED, 0 – 180W (max. 20 dimmable LED lamps)
  GLS, 0 – 180W
- *supply voltage 230V~ 50Hz*
- *2-way switch combination is possible*
- *installing several devices together in one box is only permitted if their total maximum load does not exceed the maximum power of a single dimmer*
- *one circuit allows the use of only one dimmer*
- *no built-in fuse – external fuse must be used*
- *in accordance with IEC60669-2-1*
- *screw contacts - 1.5-2.5mm²*

REGULATOR OSVJETLJENJA ROTACIJSKI R 250W 1M

☐ EM15PW
■ EM15SB
■ EM15AT
■ EM15ES
■ EM15IW

- rotacijski bez sklopke
- tip RTS34, 43 RVP, opterećenje R, 40W – 250W
- mrežni napon 230V~ 50Hz
- nije moguća kombinacija s izmjeničnom sklopkom
- povezivanje više regulatora osvjetljenja nije dopušteno
- sukladno normi EN 60669-1
- vijčano pričvršćivanje vodiča presjeka 1,5-2,5mm²
- LED indikacija

DIMMER ROTATIVE R 250W 1M

- *rotation control without switch*
- *type RTS34, 43 RVP, load R, 40W - 250W*
- *supply voltage 230V~ 50Hz*
- *2-way switch combination is not possible*
- *more dimmers combination is not allowed*
- *in accordance with EN 60669-1*
- *screw contacts 1.5-2.5mm²*
- *LED indication*