: IoT dial thermostat 2M grey

02973

IoT dial thermostat 2M grey
Dial thermostat with relay output 5(2) A 240 V~, IoT technology on Bluetooth technology 5.0 standard for the creation of View Wireless mesh system, 1 input for external temperature sensor, 100-240 V~ 50/60 Hz power supply, heating and air conditioning in ON/OFF and PID mode, class I temperature control device (contribution 1%) in ON/OFF mode, class IV (contribution 2%) in PID mode, white LED backlighting with brightness control, 100-240 V 50/60 Hz power supply, grey - 2 modules. To be completed with Eikon, Arké and Plana cover plates, for Idea with dedicated mounting frame 16723

- Compatible with Alexa, Google Home and IFTTT, using the dedicated gateway
- Configuration via “VIEW Wireless” App for Bluetooth technology system
- Hotkeys are designed for quick interaction

Product Status
3 - Active

Minimum order quantity
1 NR

Sheets, Manuals, Documentation
- Light Multilanguage instructions sheet (1471 kb)
- Foglio istruzioni multilingua Full (696 kb)
- Feuille d’instructions multilangues Full (700 kb)
- Hoja de instrucciones multilingüe Full (696 kb)
- Full multilanguage instructions sheet (692 kb)
- Πολυγλωσσικό φύλλο οδηγιών Full (858 kb)
- Mehrsprachig-Gebrauchsinformation Full (699 kb)
- Full (828 kb)
- Manuale app View Wireless (15783 kb)
- Manual app View Wireless (37645 kb)
- Manual View Wireless app (37975 kb)
- Installationsanleitung View Wireless (37475 kb)
- Manuel appli View Wireless (36800 kb)
- Εγχειρίδιο τεχνικού εγκατάστασης (37917 kb)

Video
- App View Wireless - temperature control

Drawings



Space view



Backside view



3D View

Gallery



Technical data

- **Class group**: Stats, switches and controllers
- **Class**: Room thermostat
- **Model**: On/Off
- **Type of power supply**: 230 V AC
- **Connection**: 3-/4-wire
- **With receiver**: No
- **External sensor**: Yes
- **Thermal feedback**: Parallel
- **Control characteristic**: PID
- **Suitable for heating**: Yes
- **Number of heater outputs**: 1
- **Number of cooler outputs**: 1
- **Adjustable differential**: Yes
- **Temperature readable**: Yes
- **With sound indicator**: No
- **Sensor/feeler type**: Resistance sensor
- **Mounting method**: Flush-mounted
- **Number of modules (module system)**: 2
- **With display**: Yes
- **Operation**: Turn
- **With tap water circuit**: No
- **Max. contact voltage**: 230 V
- **Max. contact load**: 5 A
- **Degree of protection (IP)**: IP30
- **Explosion-proof**: No
- **Colour**: Grey
- **RAL-number**: 7024
- **Height**: 49,00 mm
- **Width**: 44,80 mm
- **Depth**: 41,50 mm
- **Diameter**: 0 mm
- **Class of the temperature control**: IV

Certifications

- 00. CE Marking - EU
- 29. QCERT - Colombia
- 37. Marking - Morocco
- 40. Bluetooth technology
- 43. UKCA mark - Great Britain
- 92. RoHS UAE
- 99. WEEE Directive (download)

Packaging

Code 8007352657526
Quantity 1 NR
Dim. 5.7x5.3x7.7 [cm]
Weight 81.6 [g]

Code 8007352746466
Quantity 60 NR
Dim. 37.5x30x13.5 [cm]
Weight 5,209.2 [g]

Code 8007352657533
Quantity 70 NR
Dim. 39.5x30x17 [cm]
Weight 6,078 [g]

Legal

Vimar reserves the right to change at any time and without notice the characteristics of the products reported.Installation should be carried out by qualified staff in compliance with the current regulations regarding the installation of electrical equipment in the country where the products are installed.For the terms of use of the information on the product info sheet see Conditions of Use.