CCTV

DVR

AHDVR004S02A

XVR 4 INPUTS 2MP, 1TB HDD

SMART SERIE

Stand-alone 5-hybrid (AHD/TVI/CVI/CVBS/IP) DVR, 4 analog video inputs or 2 analog video inputs and 7 IP video inputs or 16 IP video inputs Stand-alone 5-hybrid (AHD/TVI/CVI/CVBS/IP) DVR, 4 analog video inputs or 2 analog video inputs and 7 IP video inputs or 16 IP video inputs (Alarm inputs/outputs from S/N xxxxxxx-001).

AHDVR004S02A

XVR 4 INPUTS 2MP, 1TB HDD

MAIN FEATURES	
Video inputs	4 BNC / 16 IP (5MP max) / 2 BNC+7 IP (5MP max)
Main video output	1 (HDMI), 1 (VGA)
Audio Inputs/Outputs	4 (RCA) / 1 (RCA), G.711u, 64 kbps
Alarm Inputs/Outputs	4/1
Video compression	H.264 / H.264+ / H.265 / H.265+ (128÷8192 kbps)
Playback / recording frame rate	BNC: 4 (5MP@6fps, 4MP@8fps, 3MP@9fps, 2MP@15fps, HD@25fps). IP: 8 (5MP), 12 (4MP), 16 (3MP, 2MP, HD) @25fps
HDD supplied size	1TB (8TB max)

SOFTWARE/FIRMWARE SPECIFICATIONS	
Operating system	Linux embedded
Recording methods	Auto, manual, scheduled, motion
Recording type	Dual streaming
Maximum number of channels being played simultaneously	BNC: 4 (5MP@6fps, 4MP@8fps, 3MP@9fps, 2MP@15fps, HD@25fps). MIX: 1 (5MP, 4MP, 3MP)@25fps, 2 (2MP@30fps), 3 (2MP@15fps). IP: 1 (5MP, 4MP, 3MP)@30fps, 4 (2MP, HD)@30fps
Protocols supported	DDNS, Comelit DNS, DHCP, FTP, HTTP, NTP, PPPoE, RTCP, RTP, RTSP, SMTP, TCP/IP, UPnP
IP assignment	DHCP, manual
Encrypted transmission	SSL
Max bandwidth (Mbps)	48
Remote control via browser	Internet Explorer
Remote control by software	Comelit Smart CMS
Remote control by mobile	app Comelit View Smart (Android, iOS)
Users connected at the same time	3
Main functions	Camera control through coax cable via UTC protocol, Watermarking, Instant playback function

FUNCTIONS	
Motion detection	396

The technical specifications are subject to change without prior notice.

AHDVR004S02A

XVR 4 INPUTS 2MP, 1TB HDD

FUNCTIONS	
Privacy zones (n°)	3
Loss of video signal	Yes
Gestion PTZ par RS485 (protocoles Pelco-P, Pelco-D)	Yes (Pelco-P, Pelco-D)
Digital effects	E-zoom
System log	Yes
E-mail notification	Yes
Pre-event recording	5÷30 seconds

HARDWARE SPECIFICATIONS	
Type of connections/ports	1xEthernet 10/100 Mbit/s, 2xUSB 2.0, 1xRS485
Fanless	Yes

GENERAL DATA	
Max absorption (W)	17
Power supply voltage (VDC)	12
Supply voltage (VAC)	100÷240, 50÷60Hz
Height (mm)	43
Width (mm)	215
Depth (mm)	260
Product weight (g)	2500
Type of finishing materials	Metallic
Product color	Black
Operating temperature (°C)	-10 ÷ 55
Operating humidity (RH max) (%)	25 ÷ 90
Supplied accessories	Power supply, Mouse
System backup	USB 2.0

The technical specifications are subject to change without prior notice.